

Otturatori senza By-Pass



Num.Art.	Inserimento in mm	Lunghezza in cm	Peso in Kg
2002001	50-100	34	0,4
200202	70-150	33	0,5
200203	100-200	51	1,5
200204	200-400	55	2,5
200205	300-600	58	3,5
200206	500-800	73	7,0
200207	500-1000	113	17,0
200208	600-1200	136	32,0

Otturatori con By-Pass



Num.Art.	Inserimento in mm	Lunghezza in cm	Peso in Kg
100101	70-150	39	1,1
100102	100-200	51	2,1
100103	150-300	61	3,5
100104	200-400	58	12,0
100105	300-600	73	21,0
100106	500-800	68	40,0
100107	500-1000	105	35,0
100108	600-1200	138	50,0

Packer di risanamento e prove di tenuta



Num.art.	Inserimento (mm)	Lunghezza mantello	Lunghezza Effettiva (mm)	Diametro (mm)	Pressione Lavoro (bar)	Attacco By-pass
503005	100-150	1000	1080	65	2,5	senza
503010	100-150	1900	1980	65	2,5	senza
503015	100-150	2500	2580	65	2,5	senza
503035	150-250	1210	1210	105	2,0	2"
503040	150-250	1900	2110	105	2,0	2"
503045	150-250	2500	2710	105	2,0	2"
503065	300-400	1000	1240	235	1,5	2"
503070	300-400	1900	2140	235	1,5	2"
503075	300-400	2500	2740	235	1,5	2"
503095	450-600	1000	1240	365	1,2	4"
503100	450-600	1900	2140	365	1,2	4"
503105	450-600	2500	2740	365	1,2	4"
503115	600-800	1400	1640	365	1,0	4"
503120	600-800	1900	2140	365	1,0	4"
503135	800-1000	1600	1870	472	0,6	4"
503140	1000-1200	1900	2130	472	0,6	4"